G30







Providing shooters with the same great magnification properties as our battle-tested G33 Magnifier at less than half the cost, this new-for-2020 product features a quick-detach fixed mount for fast and simple mounting and unmounting behind an HWS. The G30 works with all EOTECH HWS models.

Order Codes G30.FM

BLACK

OPERATION CHARACTERISTICS

Overall Length	4.0" (102 mm)
Weight	9.5 oz. (270 g)
Water Resistance	To 3 ft. (1 m)
Color/Finish	Black
Mount	1" Weaver or MIL-STD-1913 rail
Magnification	3X
Eye Relief	2.2" (55.5 mm)
Field-of-View	7.3°
Sealing	Fog-resistant internal optics

DISCLAIMERS

ALL EOTECH MATERIALS ARE FOR INFORMATIONAL PURPOSES ONLY AND DO NOT CONSTITUTE ANY BINDING OBLIGATIONS OR AGREEMENT BY EOTECH OR L3HARRIS TECHNOLOGIES, INC.

ALL CLAIMS ABOUT PERFORMANCE AND PERFORMANCE CHARACTERISTICS ASSUME NORMAL, RESPONSIBLE USAGE WITHIN THE WARRANTY PERIOD.

EOTECH RESERVES THE RIGHT TO CHANGE THE PRODUCT SPECIFICATIONS AT ANY TIME WITHOUT NOTICE.

ALL OPTICAL DEVICES ARE SUSCEPTIBLE TO TEMPERATURE VARIATIONS. EOTECH USERS THEREFORE MAY EXPERIENCE A POINT OF IMPACT SHIFT AWAY FROM THE POINT OF AIM WHEN THE SIGHT IS USED AT A TEMPERATURE SIGNIFICANTLY

DIFFERENT FROM THE TEMPERATURE AT WHICH THE SIGHT WAS ZEROED. THE TYPICAL SHIFT IS BETWEEN APPROXIMATELY 1.4 MOA AND 1.8 MOA FOR CURRENT SIGHTS.

ALL EOTECH SIGHTS EXHIBIT A VARYING DEGREE OF PARALLAX DEPENDING ON OPERATING CONDITIONS.

PATENTS — ONE OR MORE OF THESE PRODUCTS MAY BE COVERED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS: 5,374,986; 5,400,540; 5,430,967; 6,185,854; 6,190,025; 6,574,901; 7,493,722; D522,031; D568,508 AND D595,439.

THIS DOCUMENT CONSISTS OF GENERAL CAPABILITIES INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR, PART 120.10 OR EAR, PART 772.



1201 EAST ELLSWORTH RD. ANN ARBOR, MI 48108 USA +1-888-368-4656 EOTECHINC.COM

© 2019 L3Harris Technologies, Inc. EOTECH*, VUDU*, HWS* and Holo Sight* are registered trademarks of L3Harris Technologies Inc. in the United States and other countries.