



GGG-1753 AK-47 800 Meter Ghost Ring Replac. Sight



**GGG-1753
AK-47 800 Meter
Ghost Ring Rear Sight**

AK-47 800 Meter Ghost Ring Rear Sights

Installation Instructions

CAUTION: Make sure the weapon is **UNLOADED**, **CLEAR** and made **SAFE** before proceeding.

1. Remove the factory rear sight by depressing downward on the rear sight spring while sliding the rear sight assembly towards the rear.
2. Make sure the rear sight slides out on the built-in tracks of the rear sight housing.
3. Remove the elevation button from the rear sight by sliding forward off the rear sight elevation platform. Make sure to not lose the spring and button once disassembled.
4. Install the elevation button and spring onto the GG&G Ghost Ring Rear sight by sliding it onto the front portion of the sight.
5. Once the button assembly is installed, slide it to the rear of the ghost ring sight.
6. Install the GG&G Ghost Ring Rear Sight by lining the two metal tabs on the sight with the tracks on the rear sight housing.
7. Depress down on the rear sight spring and slide the rear sight into the locked position.
8. Release the spring. The rear sight will now be locked into place.
9. Test the sight by raising it up and down and by sliding the elevation button back and forth on the elevation platform.

GG&G

3602 E. 42ND STRAVENUE TUCSON AZ 85713

800-380-2540 FAX: 520-748-7583

WEBSITE: GGBAZ.COM E-MAIL: GGBAZ@AOL.COM