



**GGG-1754  
AK-47 1000 Meter  
Ghost Ring Rear Sight**

## **AK-47 1000 Meter Ghost Ring Rear Sight**

### **Installation Instructions**

**CAUTION: Make sure the firearm is UNLOADED, CLEAR and made SAFE before proceeding.**

1. Remove the factory rear sight by depressing downward on the rear sight spring while sliding the rear sight assembly towards the rear.
2. Make sure the rear sight slides out on the built-in tracks of the rear sight housing.
3. Remove the elevation button from the rear sight by sliding forward off the rear sight elevation platform. Make sure to not lose the spring and button once disassembled.
4. Install the elevation button and spring onto the GG&G Ghost Ring Rear Sight by sliding it onto the front portion of the sight.
5. Once the button assembly is installed, slide it to the rear of the ghost ring sight.
6. Install the GG&G Ghost Ring Rear Sight by lining the two metal tabs on the sight with the tracks on the rear sight housing.
7. Depress down on the rear sight spring and slide the rear sight into the locked position.
8. Release the spring. The rear sight will now be locked into place.
9. Test the sight by raising it up and down and by sliding the elevation button back and forth on the elevation platform.

**GG&G**

**3602 E. 42ND STRAVENUE TUCSON AZ 85713  
800-380-2540 FAX: 520-748-7583  
WEBSITE: GGBAZ.COM E-MAIL: GGBAZ@AOL.COM**