HYBRID COMPACT

MULTIFUNCTION THERMAL OPTIC

The Hybrid Compact (HCH50R) is the next evolution of the HYBRID series, combining advanced thermal performance with versatile functionality. It features a 50 mm F/0.9 lens and the industry's first available 10 μm thermal sensor. The 640×480 InfiRay sensor with a ≤ 15 mK NETD rating delivers exceptional thermal sensitivity and clarity. The Hybrid Compact functions as a weapon sight, thermal clip-on, or handheld monocular. Its 3.5x native magnification and 60mm eye relief provide a comfortable, immersive view. The "Fast Engine" low-latency architecture (15 ms) and 60 Hz refresh rate ensure a smooth, life-like image, improving target tracking and accuracy. A 1440×1080 AMOLED display provides a crisp image, while the integrated laser rangefinder and ballistic calculator adjust for drop based on target distance. Built-in photo and video recording with 64GB of internal storage lets you capture every detail.





NEW HCH50R

SENSOR	
Resolution	640×480
Pixel Size	10 μm
Frame Rate	60 Hz / 30 Hz
Sensor Sensitivity	≤15 mK
Image Processing	InfiRay Fast Engine Low-latency Processor
Core	InfiRay 640
OPTICS	
Objective Lens	50 mm f/0.9
Native Magnification	3.5×
Digital Zoom	8×
Field of View	7.3° × 5.5°
Detection Range	3,060 yards
Display Type	0.71-inch AMOLED
Display Resolution	1440×1080
Color Palettes	White Hot, Black Hot, Red Hot, Color, Crimson, Viridian, Violet
Picture-in-Picture	Yes
Rangefinder	Integrated 1,200 yd LRF
Eye Relief	60 mm
Diopter Range	-5 to +2
ELECTRONICS	
Onboard Recording	Video and Image
Onboard Storage	64 GB
Wireless Connectivity	Image and Video via App.
Data/Power Connector	USB-C
Power Supply	18650 Rechargeable (Two Nitecore USB-C cells included)
Max. Operating Time	7+ Hours Each
Start Up Time	<3 Seconds, Instant from Standby
PHYSICAL	
Size	9.87" × 4.05" × 3.07"
Weight	25.56 oz.
ENVIRONMENTAL & WARF	ANTY
Warranty	5 Years
Housing Material	Magnesium Alloy
Housing Color	Cerakote® Tan H-235
Mount Type	DLOC Precision Picatinny Rail Mount
Ingress Protection	IP67
Operation Temperature	-25°F – 122°F
Max Recoil Rating	1,200 G/s²






905 nm < 400 nJ 40 ns

REGISTRATION: irayusa.com/register WARRANTY: irayusa.com/warranty SUPPORT/SERVICE: irayusa.com/support

NOTE: These products may be subject to export and foreign trade control laws of the United States and may not be exported without prior approval of the U.S. Department of State. Learn more at irayusa.com/ITAR. The thermal images shown are for illustrative purposes only and may vary in real world usage. Specifications are subject to change without notice. For the most up-to-date spees, go to irayusa.com. Not responsible for typographical errors. Ver 1.00 - 202503







Like other HYBRID series models, the HCH50R can be used as a clip-on thermal (with day scope magnification up to 10°) or as a dedicated thermal weapon sight. The industry's first available 10 μ m sensor increases pixel density by 44%, providing high resolution while reducing the overall size of the unit. Powered by a 18650 cell rechargeable battery , the HCH50R includes a Bluetooth remote for seamless clip-on control and a secure DLOC Picatinny rail mount for quick, repeatable attachment. The HCH50R comes with a durable hard case for reliable protection in the field.



To visit the product webpage, scan the QR code or go to irayusa.com/hch50r



2601 SH 121, Building 3 Suite #306 Lewisville, TX 75056

800-769-7125 682-499-0047 info@irayusa.com