



MEPRO STING

Dual Wavelength Laser Pointer

The Meprolight® Sting is a weapon-mounted dual laser system designed for close-quarters battle (CQB) and night operations. The rear-facing selector switch allows users to choose from visible low, visible high, IR low, and IR high, using the included remote pressure switch or turning the device off.

The Sting utilizes a precise single aiming mechanism to simultaneously boresight both lasers. Accurately zero your weapon in daylight or nighttime conditions. The system comes with a quick-release MIL-STD 1913 reversible Picatinny mount so users can accommodate weapon-mounted white/IR lights. A press-to-lase (PTL) cable can be attached anywhere on the firearm, enabling users to engage targets either momentarily or continuously.

The Mepro Sting is a low-profile system, allowing it to sit lower on the rail, so as not to impede the shooter's sight picture when mounted at the 12 o'clock position. Designed for combat. Proven in combat.

PROVEN ADVANTAGES

- Single zeroing mechanism zeroes both lasers simultaneously
- Selectable Class 3 High and coaxial-mounted Class 2 Low visible/IR laser output power
- Momentary or constant lasing modes
- Rear visual LED confirms mode selection
- Powered by single, AA battery
- Reversible MIL-STD 1913 picatinny mount
- MIL-STD 810 qualified

SPECS

- Laser pointers: Red & IR
- Weight: 240 g (8.5 oz.) w/o battery
- Wavelength: Visible ~635nm / IR ~850nm
- Beam divergence: < 0.3 mRad (dot)
- Power Source: 1x "AA" (Alkaline/Lithium/NiMH)
- LED indicator: IR Laser- Green, Red Laser- Red, Low battery- Flashing Red
- Weapon mount: MIL-STD-1913- Picatinny (quick release)
- Environmental: MIL-STD-810
- Dimensions: (L x W x H): 109x77x40 mm (4.3 x 3 x 1.6 in.)

Product

MEPRO STING-DUAL BEAM
LASER POINTER

P/N

03050006

UPC

840103151779



Laser Pointer



Lightweight



MIL-STD



Withstands Heavy
Recoil



MEPROGUARD
Warranty