

1535

Air

Carry-On Case

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 40 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started.

the world, and we're just getting started.
With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve Keeps water and dust out while balancing air pressure
- Maximum airline carry on size*
- Retractable extension handle
- Super-light proprietary $HPX^{2 \text{ m}}$ Polymer
- · Business card holder
- · Quiet rolling stainless-steel bearing wheels
- * Check with your airline for exact measurement requirements.



CONFIGURATIONS







1535NF



1535WD With Padded Dividers



1535TPWith TrekPak Divider System



1535WF With Foam



1535AIRTPF Hybrid Case

DIMENSIONS

Interior (L x W x D) 20.39 x 11.20" x 7.21 (51.8 x 28.4 x 18.3 cm) Exterior (L x W x D) 21.96 x 13.97" x 8.98 (55.8 x 35.5 x 22.8 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 5.21" (13.2 cm)

 Total Depth
 7.21" (18.3 cm)

 Int Volume
 0.95 ft³ (0.027 m³)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS

Black

Yellow

Silver

Orange

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 $\underline{sales@pelican.com} \bullet \underline{www.pelican.com}$

WEIGHT

Document created on 05-28-19

 Weight With Foam
 9.98 lbs (4.5 kg)

 Weight Empty
 8.69 lbs (3.9 kg)

 Buoyancy
 64.80 lbs (29.4 kg)

TEMPERATURE

Minimum Temperature -60°F (-51.1 °C)

Maximum Temperature 160°F (71.1 °C)

FOAM PROPERTIES

Layer 1 (Lid)2.03" ConvoluteLayer 2 (Base)3.75" Pick N Pluck

Layer 3 (Base) 1.44" Pad

OTHER

Wheels 2

ACCESSORIES