



# 1930

## L1™

With a long lamp life and extended battery burn time, you won't be left in the dark with the L1™ flashlight. The polycarbonate body is resistant to chemicals, water and corrosion. The convenient tail switch for constant on/momentary is easy to operate. The L1™ is perfect for close quarter use. Packaged with 4 LR 44 1.5V alkaline coin cells, a break-a-way safety lanyard, and colored lens discs to preserve night vision. This handy flashlight offers a lot for its size.


- Built Pelican tough
- Super bright LED beam
- Unconditional Lifetime Guarantee of Excellence
- Security Lanyard



## CONFIGURATIONS



**1930**  
Standard



**1930M**  
Merchandiser Display

## DIMENSIONS

|        |                |
|--------|----------------|
| Length | 2.64" (6.7 cm) |
|--------|----------------|

## MATERIALS

|                         |                    |
|-------------------------|--------------------|
| Body                    | Polycarbonate (PC) |
| O-Ring                  | Ethylene Propylene |
| Lens                    | Polycarbonate (PC) |
| Shroud                  | Xenoy              |
| Contact Spring Retainer | Phosphore Bronze   |

## COLORS

|                                                                                                            |                                                                                           |
|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
|  High Visibility Yellow |  Black |
|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|

## LIGHT SPECS

|           |     |
|-----------|-----|
| Lamp Type | LED |
|-----------|-----|

# POWER

|                    |          |
|--------------------|----------|
| Battery Size       | LR 44    |
| Battery Type       | Alkaline |
| Battery Quantity   | 4        |
| Batteries Included | yes      |
| Volts              | 6.0v     |

# WEIGHT

|                          |                |
|--------------------------|----------------|
| Weight With Batteries    | 0.9 oz (26 gr) |
| Weight Without Batteries | 0.6 oz (17 gr) |
| Packaged Weight          | 0.8 oz (23 gr) |

# SWITCH


|             |                  |
|-------------|------------------|
| Switch Type | Push Button Tail |
| Light Modes | On / Off         |

# CERTIFICATIONS

|                      |
|----------------------|
| Class I, Division 2  |
| Class II, Division 2 |
| Class I, Division 1  |
| IECEx ia             |

# OTHER

|              |     |
|--------------|-----|
| Minimum Pack | 12  |
| Military     | yes |
| Package Code | C   |

| FL1 STANDARD                                                                        | HIGH         |
|-------------------------------------------------------------------------------------|--------------|
|  | 12<br>LUMENS |
|  | 4h 15mins    |
|  | 17m          |
|  | 70cd         |
|  | IPX4         |

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

---

# ACCESSORIES

*Document created on 06-13-19*

---