



2360 (Gen 5)

Tactical Flashlight

If you like the convenience of AA alkaline batteries, but need the performance of lithium batteries, the 2360 LED is the light for you. Using 2 standard AA alkaline batteries, the new 2360 LED emits a peak output of 375 lumens. The 2360 includes 3 modes – High / Strobe / Low and allows the user to select from 4 selectable programs. With the included 29 lumen low beam a run time of up to 13 hours will support close up use and any extended time needs. A strobe mode is also included for tactical or signaling purposes. The built-in battery level indicator ensures you will not be left in the dark.

Constructed with the most durable of materials: an aerospace grade aluminum body and an impact resistant LED lamp module, the 2360 LED keeps you on point without equipment failure.

High, Low and Strobe light output is available with a push of the tail button. It features a non-slip textured body for secure handling. The removable pocket clip offers alternative carry options.



- 4 Selectable Programs
- Pelican Products, Inc.'s Lifetime Guarantee
- 375 lumens
- 3 modes High / Strobe / Low
- Battery Level Indication
- 2 AA Batteries (included)

DIMENSIONS

Length	6.20" (15.7 cm)
--------	-----------------

MATERIALS

Body	Aluminum with Type II Anodized
O-Ring	EPDM
Lens	Polycarbonate (PC)
Shroud	Aluminum with Type II Anodized
Clip	High Carbon Steel

COLORS

■ Black

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	2
Batteries Included	yes
Battery Level Indicator	Level indicator
Volts	3.0v

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

WEIGHT

Document created on 06-10-19

Weight With Batteries 5.4 oz (153 gr)

Weight Without Batteries 3.7 oz (105 gr)

SWITCH






Switch Type Momentary Push Button

Light Modes High / Strobe / Low

OTHER

Minimum Pack 6

Package Code B

FL1 STANDARD	HIGH	LOW
	375 LUMENS	29 LUMENS
	2h 30mins	13h 0mins
	192m	53m
	9187cd	705cd
	IPX8 (1m)	

ACCESSORIES