



# 3700

## Big Ed™

Right Angle Light

Designed for the firefighter, the Big Ed™ is the choice of flashlight for the turnout gear. The unbreakable ABS body resists chemicals, water, and corrosion. Rubber side grips prevent slipping and the push button switch on the side is easy to operate, even with thick gloves. For hands-free use, a heavy duty stainless steel clip is built in. The 3700 uses a hi-intensity Xenon lamp that produces a beam strong enough to cut through thick smoke and dust. A back-up emergency lamp is housed behind the reflector. Battery replacement is easy with its quick change battery ejection system. The Big Ed™ is powered by 4 C alkaline cells.

Personalized nameplate service available

- Built Pelican tough
- Super bright Xenon beam
- Unconditional Lifetime Guarantee of Excellence




## DIMENSIONS

**Length** 7.00" (17.8 cm)

## MATERIALS

**Body** ABS  
**O-Ring** Ethylene Propylene  
**Lens** Polycarbonate (PC)  
**Shroud** ABS  
**Clip** Stainless Steel  
**Contact Spring Retainer** Stainless Steel / Phosphore Bronze / Brass Nickel Plate

## COLORS

 High Visibility Yellow

## LIGHT SPECS

**Lamp Type** Incandescent (Krypton)

## POWER

**Battery Size** C  
**Battery Type** Alkaline  
**Battery Quantity** 4  
**Volts** 6.0v

## WEIGHT

**Weight With Batteries** 20.3 oz (575 gr)  
**Weight Without Batteries** 10.5 oz (298 gr)  
**Packaged Weight** 13.8 oz (391 gr)

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

# SWITCH

Document created on 06-21-19






**Switch Type** Push Button  
**Light Modes** On / Off

# CERTIFICATIONS

Class I, Division 2

# OTHER

**Minimum Pack** 1  
**Military** yes  
**Package Code** B

FL1 STANDARD	HIGH	BACKUP
	39 LUMENS	25 LUMENS
	6h 15mins	8h 30mins
	98m	51m
	2437cd	684cd
	IPX4	

# ACCESSORIES