

SCHMIDT ⓧ BENDER

PRECISION SNIPER RIFLE LIMITED EDITION



34
mm

ZS
ZERO STOP

LT
LOCKING
TURRETS

DT
DOUBLE TURN

5
ZOOM



RRP \$ 3975



5-25x56 PM II PSR

- 5-25x56 PM II LP LT CM CCW
- TREMOR2 RETICLE
- SPECIAL PRECISION SNIPER RIFLE CONFIGURATION
- LIMITED EDITION OF ONLY 300 PIECES

Purchase a limited edition Precision Sniper Rifle configuration with a valuable and numbered emblem

Schmidt & Bender was awarded the coveted **Precision Sniper Rifle (PSR)** military day scope contract, in 2011, for the 5-25x56 PM II™ model. The 5-25x56 PM II™ was tested, tortured, scrutinized, and evaluated heavily by U.S. Special Forces before being selected by this most elite military group. Since then, U.S. Special Forces of the Army, Navy, Air Force, and Marines have been supplied with the 5-25x56 PM II™ PSR day scope.

Continued on back of page...

For more Information about Schmidt & Bender products visit www.schmidt-bender.com

SCHMIDT Ⓢ BENDER

PRECISION SNIPER RIFLE LIMITED EDITION



From the time the contract was awarded, Schmidt & Bender has been asked, repeatedly, to offer these riflescopes in the same configuration to the commercial markets. Beginning in late 2016, and into 2017, Schmidt & Bender has released the **Limited Edition PSR 5-25x56 PM II™** riflescopes to the civilian sporting markets. These riflescopes incorporate the same reticle, adjustments, and locking mechanisms as the original PSR riflescopes. The Limited Edition production run will consist of 300 pieces worldwide.

If you prefer a riflescope like those used by U.S. Special Forces, the **Limited Edition PSR 5-25x56 PM II™** model is a riflescope custom built and hand-crafted in Germany to meet the application. These can only be found at Schmidt & Bender Authorized Stocking Dealers. Don't settle for less. Demand Schmidt & Bender.

1. Dimensions & properties

Weight:	1056 g/37.25 ounces
Length:	417.5 mm/16.44 inches
Main tube diameter:	34 mm

2. Optical Data*

Magnification:	5.0 - 25.0
Objective diameter:	56 mm
Field of view:	17.38 ft - 4,92 ft / 100 yd
Exit pupil:	0.43" - 0.09
Eye relief:	3.54"
Twilight factor:	16.7 - 34.4
Transmission:	90 %
Focal plane:	1 st

3. Adjustments*

Dioptr:	-3 dpt. bis +2 dpt.
Adjustment range elevation turret:	260 cm / 64 MOA
Adjustment range windage turret:	± 60 cm / ± 14 MOA
Parallax:	10 m - ∞

4. Available configurations*

a.) Turrets:	
Elevation:	Double Turn (with locking function)
Windage:	Single Turn (with zero stop and locking function)

Turret configurations

Elevation	Windage
1 cm/.1 mil counter clockwise	1 cm/.1 mil counter clockwise

b.) Colors:

- Pantone 7504M

c.) Illumination

- Illuminated

d.) Reticles

- Tremor2

5. Sale

RRP	\$ 3975.00
Item No.	677-946-532-B2-A8B20

* all data is subject to change

