



ELECTRO-OPTICS

XRAY5™ & FOXTROT2R-LF COMBO

ADVANCED RED DOT SIGHT & WEAPON MOUNTED WHITE LIGHT



XRAY5™ & FOXTROT2R-LF COMBO

ADVANCED RED DOT SIGHT AND WEAPON MOUNTED WHITE LIGHT

SOXF53320 | SOXF54320

XRAY5

- ▶ **ULTIMATE DURABILITY** - Ruggedized Solid-State Construction With No Moving Parts, featuring a rigid 225-pixel red dot matrix, impervious to shocks and impacts
- ▶ **UNMATCHED CLARITY AND ACCURACY** - Patented Zero Distortion Optical System™, with low deck height for backup co-witness with standard-height sights
- ▶ **ADVANCED CAPABILITIES** - Including Digital Zero™, Multiple Zero Profiles, LightFight™, and Round Counter™, fully customizable through the free XRAY5 App
- ▶ **LIGHTFIGHT™** - SIG SAUER sights and lights equipped with Bluetooth™ LightFight™ automatically increase reticle brightness when weapon light is activated
- ▶ Available Mounting Footprints: DeltaPoint® PRO (SOX53300), Shield RMSc (SOX54300)
- ▶ A fully enclosed, sealed, and Argon-purged optical system, for ultimate protection from the elements
- ▶ A 7075 Aluminum housing and a Grade 5 Titanium shield for the roof lens.
- ▶ 15 brightness settings, with 2 of the settings optimized for use with Gen 3+ NV devices
- ▶ A side-mounted CR2032 battery compartment with a threaded battery cap, for easy battery changes without the need to remove the optic from the firearm
- ▶ Minimum continuous runtime of 10,000 hours, at medium brightness setting
- ▶ MOTAC™ (Motion Activated Illumination)
- ▶ D.A.R.C. (Dark Adaptive Reticles & Coatings)
- ▶ Designed, developed, tested and assembled in the USA

FOXTROT2R LIGHTFIGHT

- ▶ **LIGHTFIGHT™** - SIG SAUER sights and lights equipped with Bluetooth™ LightFight™ automatically increase reticle brightness when weapon light is activated
- ▶ Pairs with XRAY5 Advanced Red Dot Sight
- ▶ Assembled in the USA
- ▶ Ambidextrous Activation Paddles with Momentary Mode, Latching Mode, and Threshold Mode
- ▶ Programmable Activation, 3 Separate Modes Chosen by the User
- ▶ 4-Position Sliding Rail Inserts For a Customizable Fit
- ▶ IPX-7 Waterproof rating

LIVE-FIRE RATING

Tested to exceed
100,000 rounds

WATERPROOF RATING

IPX8 up to 40 Meters (132 feet)

DROP TEST RATING

Tested to survive
multiple drops up to
8 feet onto concrete

SKU#:	SOXF53320	SOXF54320
MOUNTING FOOTPRINT:	PRO	COMPACT
UPC:	798681755509	798681755523



A fully enclosed, sealed and purged optical system, for ultimate protection from the elements



a 225-pixel red dot matrix allows digital zeroing by selecting individual pixels, meaning no moving parts and unmatched durability




Rugged 7075 Aluminum housing and Grade 5 Titanium top cover to protect the optical lens

XRAY⁵™ & FOXTROT2R-LF COMBO

ADVANCED RED DOT SIGHT & WEAPON MOUNTED WHITE LIGHT

PRODUCT DETAILS		XRAY5		
SKU#	SOX53300		SOX54300	
MOUNTING FOOTPRINT	PRO		COMPACT	
HOUSING MATERIAL	7075 ALUMINUM, AND A GRADE 5 TITANIUM LENS SHIELD			
HOUSING FINISH	BLACK ANODIZED			
CLEAR APERTURE DIAMETER (MEASURED DIAGONALLY)	24 MM			
LENS MATERIAL	GLASS			
LENS TYPE	ROOF ASPHERE			
BATTERY TYPE	CR2032			
BATTERY LOCATION	SIDE			
BATTERY ACCESS	SLOTTED THREADED CAP			
BATTERY LIFE IN HOURS AT MEDIUM SETTING	UP TO 10,000 HOURS			
EMITTER TYPE	225-PIXEL (15X15) LED MATRIX			
WINDAGE ADJUSTMENT RANGE	80 MOA			
ELEVATION ADJUSTMENT RANGE	80 MOA			
ADJUSTMENT METHOD	DIGITAL (BUTTON PRESSES OR XRAY APP)			
BRIGHTNESS ADJUSTMENT SETTINGS	15 (13 DAY, 2 NV)			
RETICLE	3.5 MOA RED DOT			
WATER RESISTANCE	IPX-8 UP TO 40 METERS (132 FEET)			
DROP RATING	TESTED TO SURVIVE MULTIPLE DROPS UP TO 8 FEET ONTO CONCRETE			
MEASUREMENTS	SOX53300		SOX54300	
	IMPERIAL	METRIC	IMPERIAL	METRIC
OVERALL LENGTH	1.9 IN	48.26 MM	1.74 IN	44.20 MM
OVERALL HEIGHT	1.17 IN	29.72 MM	1.20 IN	30.48 MM
OVERALL WIDTH	1.32 IN	33.53 MM	1.32 IN	33.53 MM
WEIGHT W BATTERY	1.45 OZ	41.11 G	1.35 OZ	38.27 G

PRODUCT DETAILS		FOXTROT2R LIGHTFIGHT	
SKU#		SOF2RLF01	
PEAK LUMENS		700	
PEAK CANDELA		20,000	
RUNTIME IN HOURS		UP TO 1.5 HOURS	
ACTIVATION		AMBIDEXTROUS ACTIVATION PADDLES WITH MOMENTARY MODE, LATCHING MODE, AND THRESHOLD MODE	
BATTERY TYPE		(1) 16340 HIGH-CAPACITY LI-ION RECHARGEABLE BATTERY OR (1) CR123A BATTERY	
WATERPROOF RATING		IPX-7	
MEASUREMENTS		IMPERIAL	METRIC
OVERALL LENGTH		2.98 IN	75.69 MM
OVERALL HEIGHT		1.31 IN	33.40 MM
OVERALL WIDTH		1.18 IN	30 MM
WEIGHT W/ BATTERY		2.9 OZ	82.21 G



SCAN QR CODE
TO DOWNLOAD
XRAY APP



SCAN QR CODE
FOR FULL
PRODUCT DETAILS

SIG SAUER®