



Sightmark Triple Duty 8.5-25x50 Riflescope

SM13011



DESCRIPTION

Get closer to your target with the Sightmark® Triple Duty 8.5-25x50 MDD Riflescope. Tested and recommended by the National Tactical officers Association, this high-power riflescope features a large 50mm objective lens and a Mil-Dot reticle that offers bright, crisp images at long distances. Designed for superior range estimation and long-distance shooting, the 8.5-25x50 Riflescope utilizes cutting-edge glass with fully multi-coated optics for exceptional clarity. The one-piece 30mm tube offers a wide field-of-view and fully multi-coated optics for a bright, crisp image. O-ring sealed and nitrogen-purged, the Triple Duty 8.5-25x50 Riflescope is both fog proof and water resistant. This precision scope features a parallax adjustment knob and oversized, locking windage and elevation turrets with 1/8-inch MOA clicks, providing an additional level of accuracy and ensuring that the scope stays zeroed. The Triple Duty series of riflescopes are complimentary to any shooter's arsenal.

FEATURES

Weatherproof, shockproof, fogproof
Windage/Elevation adjustment lock
Second focal plane reticle (true at 10x)

Etched reticle
30mm main tube
Red and green reticle illumination

SPECIFICATIONS

Reticle	Mil-Dot
Reticle, Type	Etched
Reticle, Color	Black and green
Reticle, Illuminated	yes
Setting, Brightness	0 - 5
Finish/Color	Matte black
Magnification	8.5 - 25
Diameter, Objective Lens	50
Diameter, Eyepiece	1.45 / 37
Diameter, Exit Pupil	5.8 - 2.0
Eye Relief	3.88 - 3.46 / 98.6 - 88
Field of View	4.89 - 1.66
Field of View	14.66 - 4.97
Diopter Adjustment	-3 to 2
Diameter, Tube	30
Tube Piece (single/two)	single
Parallax Setting	10 to infinity
Windage Range of Adjustment	60
Elevation Range of Adjustment	60
Windage & Elevation, Lock	yes

MOA Adjustment	1/8
Maximum Recoil	1,200
Battery Type	CR2032
Battery Life	(high) 80 - (low) 150
Battery Voltage	3
Sunshade	yes
Nitrogen Purged	yes
Shockproof	yes
Fog Proof	yes
Focal Plane	2nd
IP Standard	IP66
Body Material	6061 Aluminum
Lens Coating	Fully multi-coated
Mount Type	Weaver
Operating Temp, \diamond F/ \diamond C	-20 to 140 / -29 to 60
Length	15.94 / 405
Width	3.34 / 85
Height	2.99 / 76
Weight	28.2

Print friendly version