



3U iSeries Injection Molded Fly Rack - 20"

3i-2424M103U



Featuring both injection molded cases and racks, our improved waterproof Fly Racks are lighter in weight and more affordable than previous models, all without compromising strength or

SKB's injection molded rack frames are manufactured alongside our iSeries cases in Orange, California. Rack frames are removable and fit easily into SKB's iSeries cases, where they are protected by high quality PE foam that provides space for protruding knobs and

At less than half the weight of standard shock racks, SKB Fly Racks are the perfect solution for flying or shipping delicate equipment. Convenient in-line wheels and a push button release pull handle provides easy

This case comes with Travel Sentry® Approved locking latches installed. Using Travel Sentry® Approved locks allows your luggage to be opened, inspected, and relocked by TSA authorities without damage. For more information, visit

SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket-sealed, water and dust tight, submersible design (MIL-C-4150J). Other standard features include a molded-in hinge, patented Trigger Latch® System, comfortable, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD-648C), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD

FEATURES

- 3U Removable injection molded shock rack
- 20 inch rack
- Interior foam
- Ultra high-strength polypropylene copolymer resin case
- UV, solvent, corrosion and fungus resistant (MIL-STD
- Complete gasket seal makes these cases absolutely watertight (MIL-STD-C-4150J)
- Automatic ambient pressure equalization valve
- Molded-in
- This case comes with Travel Sentry® Approved locking latches installed. Using Travel Sentry® Approved locks allows your luggage to be opened, inspected, and relocked by TSA authorities without damage. For more information, visit
- Rubber over-molded cushion grip
- Locking loops to accommodate a customer supplied
- Built-in wheels and pull

SPECIFICATIONS

Exterior	Hard	-
Built In Wheels or Casters	Yes	-
Rack Units	3	-
Rail To Rail	20 in	50.80 cm
Product Weight	33.67 lb	15.27 kg
Exterior Length	26.5 in	67.31 cm
Exterior Width	26.56 in	67.46 cm
Exterior Height	11.65 in	29.59 cm
Carton Length	27 in	68.58 cm
Carton Width	27 in	68.58 cm
Carton Height	12.5 in	31.75 cm
Shipping Weight	36.45 lb	16.53 kg

AVAILABLE CONFIGURATIONS

3i-2424M103U

Black

-