



PRODUCT FACT SHEET

SLEDGE™ HEADLAMP RUGGED RECHARGEABLE HEADLAMP

DESCRIPTION: The Sledge™ is a rugged, rechargeable, flood headlamp designed for versatility and performance for industrial applications and outdoor use. It features dual power LEDs and offers four total output modes. Powered by the SL-B26® protected Li-Ion USB rechargeable battery pack, it can also operate on two CR123A lithium batteries. Packaged with a USB-C charging cable, elastic head and rubber head hardhat straps, and one SL-B26® battery.

CASE MATERIAL: Tough Polycarbonate thermoplastic construction with aluminum faceplate. Available in Black.

DIMENSIONS: Height: 1.57 in. (4.0 cm) Width: 3.74 in. (9.5 cm) Front to Back: 1.73 in (4.4 cm)

WEIGHT: 4.6 oz (121.9 grams) with SL-B26® battery pack

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Regulated output for consistent lumen performance over the battery life.

ON/OFF: Multi-function push button switch. High, Medium, Low and Off

THRO® Mode: Press and hold the button for 3 seconds while light is on, after 60 seconds, light reverts to prior mode

NOTE: If more than two seconds pass between button presses, the next press will turn the light off

RUN TIME: See charts. All claims to 10% of initial lumen output.

BATTERY: One (1) Streamlight® SL-B26® protected Li-Ion USB rechargeable battery pack with on-board safety control, 2600mAh, rechargeable up to 500 times. Recharges in 5 hours.

FEATURES:



Aluminum faceplate.

45° tilting head.

IPX4 rated for water resistant operation.

2 meter impact resistance tested.

Low battery indicator - Headlamp blinks twice at regular intervals for the last 15 minutes of "usable" light.

Serialized for positive identification.

Rubber

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS: CE UK Meets applicable United Kingdom and European Community Directives

OPTIONAL

ACCESSORIES: Hardhat clips, rubber hardhat and elastic head straps

	FL1 STANDARD	THRO	HIGH	MED	LOW
OUTPUT		1000 LUMENS	600 LUMENS	300 LUMENS	100 LUMENS
RUNTIME		60s	4h15min	9h15min	13h
DISTANCE		110m	85m	58m	35m
INTENSITY		3000cd	1800cd	850cd	310cd

Performance Tested with SL-B26® Battery

All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 07/21/2025

Revised: 09/19/2025

Rev: 1

Made in China

Document #442